



NOTES:

MATERIAL:

- 1. HOUSING MATERIAL :PBT, PA66(UL 94V-0)
- 2. CONTACT MATERIAL :ROUND PINS-0.46mm DIAMETER PHOSPHOR BRONZE; GOLD PLATING OVER NICKEL

ELECTRICAL/PHYSICAL:

- 1. VOLTAGE RATING :125 VAC RMS
- 2. CURRENT RATING :1.5 AMP
- 3. CONTACT RESISTANCE :30 MILLIOHMS MAX2
- 4. INSULATION RESISTANCE :500 MEGOHMS MIN @500V DC
- 5. DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 60Hz 1MIN
- 6. DURABILITY :750 CYCLES MIN
- 7. TEMPERATURE :-40 ° C/+85° C

52-01 - X X - X X X X

No. Of Positions 4, 6 or 8	No. Of Contacts 2, 4, 6 or 8	Panel 0-w/0 Panel 1-w/Panel	Housing Peg 1-Split Peg 2-"L" Peg	Plastic 1-PBT 2-PA66	Color 1-Black 2-Gray 3-Other	Gold Plating 1-G/Fu" 2-3u" 3-6u" 4-15u" 5-30u" 6-50u"
-------------------------------	---------------------------------	-----------------------------------	---	----------------------------	---------------------------------------	---

NOT SCALED
DRAWING

TOLERANCE UNLESS
OTHERWISE NOTICE

INCH

MM

DR. Nina

DATE

HENGLIAN ELECTRONIC TECHNOLOGY CO., LTD

THIRD ANGLE PROJECTION

LINEAR

RADIL

CKID Jack

MAY-06-12

恒连电子科技有限公司

RJ11 TOP ENTRY PCB JACK

DWG. NO. HL012052001

ANGLE +0° 30'

APPD Jack

MAY-06-12

http://www.chinarj45.com