



NOTES:

MATERIAL:

- 1. HOUSING MATERIAL :PBT PA66(UL 94V-0)
- 2. CONTACT MATERIAL :ROUND PINS-0.46mm DIAMETER PHOSPHOR BRONZE; GOLD PLATING OVER NICKEL

ELECTRICAL/PHYSICAL:

- 1. VOLTAGE RATING :125 VAC RMS
- 2. CURRENT RATING :1.5 AMP
- 3. CONTACT RESISTANCE :30 MILLIOHMS MAX2
- 4. INSULATION RESISTANCE :500 MEGOHMS MIN @50V DC
- 5. DIELECTRIC WITHSTANDING RISTTANCE :1000V AC RMS 60HZ-1MIN
- 6. DURABILITY :750 CYCLES MIN
- 7. TEMPERATURE :-40 ° C/+85 ° C

52-01 - X - X - X - X

No. Of Positions	No. Of Contacts	Panel	Housing Peg	Plastic	Color	Gold Plating
4, 6 or 8	2, 4, 6 or 8	0-w/0 Panel 1-w/Panel	1-Split Peg 2-"L" Peg	1-PBT 2-PA66	1-Black 2-Gray 3-Other	1-G/Fu" 2-3u" 3-6u" 4-15u" 5-30u" 6-50u"

Rj11 or Rj12 TOP ENTRY PCB JACK	NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE	HENGLIAN ELECTRONIC TECHNOLOGY CO., LTD 恒连电子科技有限公司 <a href="http://www.chinarj45.com">http://www.chinarj45.com</a>
	THIRD ANGLE PROJECTION	LINEAR	MM INCH	MM INCH	Nina Jack	MAY-06-12 MAY-06-12	
DWG. NO.	MM INCH	ANGLE +0° 30'	RADIL	+0.45 -0.15	APP'D Jack	MAY-06-12	
HL012052002							